

General Catalogue

High Speed Doors



GIOVI
DOORS

www.giovidoors.com



GIOVI S.r.l. is a dynamic company founded in 1987 by the Rosso family, becoming one of the main leaders in the Italian market in the equipment manufacturers sector and electrical panels for the machinery control and in the building field. For years GIOVI served Italian and international companies as private labels in the High Speed industrial doors sector, providing them control panels which are the heart of the door functionality.

In order to respond to the market demands and needs, GIOVI has launched a new department dedicated to the production of industrial high-speed doors called **GioviDoors**, with employees that have more than 20 years of experience in this specific sector.

Giovi doors are guaranteed for 2 years, and are designed to be installed in a easy way with a duration life of at least 1,250,000 cycles.

Thanks to its internal organization **GioviDoors** is able to respect delivery times as well as to provide various services and assistance. Elements that represent a real economic advantage both for the end customer and for our dealer or maintenance partners, guaranteeing low management costs.

The range of products has been designed according to specific requests in order to solve the various problems in the various industrial sectors.

Our range is constantly updated in several sector and products:

- ✓ heavy industry, warehouse, supermarkets, food, logistics, cranes, laboratories and clean rooms, automotive, composting, car washes, shipbuilding, hospitals, temperature-controlled environments, ship hangars, aeronautics, space and mining.
- ✓ the Technical Staff, within the company, is able to design and manufacture high-speed doors at the customer's request, not forgetting the After Sales service able to take care of the installation and maintenance of all doors.
- ✓ the high-quality components and materials used guarantee maximum safety and durability.
- ✓ The products are certified according to the standards currently in force for CE regulations and tested before the delivery phase.

F MASTERPACK



Sectors of use



Airport



Agriculture



Shipyards



Hangar



Industry



Heavy Industry



Mining



Aerospace



Waste Treatment

Stainless steel variant for sectors in contact with liquids



Max Dim WxH:

20000 x 15000 mm



Speed:

up to 1 m/s



Wind Class:

Class 3



Temperature:

-10 to +70 ° C



Curtain:

up to 1200 gr/m²

Variant: F Simplepack (possibility of having it without casing)

F MasterPack is the folding door, available in different sizes for gates of passage of standard or special vehicles.

The standard equipment includes all the elements for its installation as well as to a complete standard equipment for functionality and safety.

F MasterPack are supplied with pre-wired electrical system, motor / panel, safety barriers or photocells and accessories already positioned. It is perfect for protecting effectively an internal environment from the external one maintaining, a controlled temperature, with a wind protection (in class 2 for the standard model up to wind class 4 but it is considered as an **F Basic Special**). With its mechanics simplified is the perfect product for those looking for a door that lasts over time and with zero routine maintenance. All **GioviDoors** products are certified according to the product standard UNI EN13241-1.

F MASTERPACK

TECHNICAL SPECIFICATIONS

Environment	Internal and External		Curtain:	Standard: Curtain PVC 930 gr/m ²
Max size	W 20000 mm x H 15000 mm			Optional: - Curtain: PVC fabric 1200 gr/m ² - Insulated 3 mm - Translucent
Speed (adjustable)	Maximum opening speed up to 1 m/s			
	Closing speed 1 m/s			
Wind resistance	Standard CLASS 2. Max Up to Class ven-to 3 a seconda delle misure			
Motor	Three-phase self-braking 230V or 400V			
Control panel	With push-button panel, mushroom head and current switch	Window	Standard: No section or up to 2 sections	
Opening system	Standard: Button on the panel and one on the opposite side		Optional: over to 2 sections possibility of variants, sizes and formats a depending on the door measurements	
	Optional: - Touchless button - Radio Remote Control - Magnetic Loop - Radar - Traffic Light - Photocells - Micro Switch - Anemometer - Numeric keyboard	Standard 1 : Man in Attendance		
	Crankcase / Motor	Standard: Galvanized steel	Standard 2 : Photocell and safety edge	
Optional: - Powder coated steel - Steel INOX 304/316		Standard 3 : Light Curtain		
			Optional: - UPS - Acoustic Alarm - Counterweight	
		Operating temperature	From -30°C to + 70°C	
		Life cycles	1.250.000	

RAL Standard for insulated Curtain

RAL Standard for Curtain

