

General Catalogue

High Speed Doors



GIOVI
DOORS

www.giovidoors.com



GIOVI S.r.l. is a dynamic company founded in 1987 by the Rosso family, becoming one of the main leaders in the Italian market in the equipment manufacturers sector and electrical panels for the machinery control and in the building field. For years GIOVI served Italian and international companies as private labels in the High Speed industrial doors sector, providing them control panels which are the heart of the door functionality.

In order to respond to the market demands and needs, GIOVI has launched a new department dedicated to the production of industrial high-speed doors called **GioviDoors**, with employees that have more than 20 years of experience in this specific sector.

Giovi doors are guaranteed for 2 years, and are designed to be installed in a easy way with a duration life of at least 1,250,000 cycles.

Thanks to its internal organization **GioviDoors** is able to respect delivery times as well as to provide various services and assistance. Elements that represent a real economic advantage both for the end customer and for our dealer or maintenance partners, guaranteeing low management costs.

The range of products has been designed according to specific requests in order to solve the various problems in the various industrial sectors.

Our range is constantly updated in several sector and products:

- ✓ heavy industry, warehouse, supermarkets, food, logistics, cranes, laboratories and clean rooms, automotive, composting, car washes, shipbuilding, hospitals, temperature-controlled environments, ship hangars, aeronautics, space and mining.
- ✓ the Technical Staff, within the company, is able to design and manufacture high-speed doors at the customer's request, not forgetting the After Sales service able to take care of the installation and maintenance of all doors.
- ✓ the high-quality components and materials used guarantee maximum safety and durability.
- ✓ The products are certified according to the standards currently in force for CE regulations and tested before the delivery phase.

MASTERROLL



Sectors of use

- Automotive
- GDO
- Industry
- Warehouse
- Hospital

Stainless steel variant for sectors in contact with liquids

Max Dim WxH: 6000 x 6000 mm	Speed: up to 1,2 m/s	Wind Class: Class 2	Temperature: -10 to +70 ° C	Curtain: up to 1200 gr/m ²

Variant: Simple Roll (possibility of having it without casing)

The **MasterRoll** is a rolling door with tubular inserts, which thanks to the brushes on the uprights offers perfect thermal insulation for applications where one is not required advanced technology and strong wind resistance.

MasterRoll fits perfectly for small to medium internal hall separations and thanks to its sections allows the installation of visual sectors for perfect vision. Strong and performing, it is suitable for any workplace, ideal for defending an indoor temperature-controlled environment such as industries and warehouses.

With its simple mechanics it is the perfect door for those looking for a door that lasts over time and with zero routine maintenance.

MASTERROLL

TECHNICAL SPECIFICATIONS

Environment	Internal and External		Curtain:	Standard: Curtain PVC 930 gr/m ²
Max size	W 6000 mm x H 6000 mm			Optional: - Curtain: PVC fabric 1200 gr/m ² - Insulated 3 mm - Insulated 8 mm - Translucent - FDA (Antibacterial) - Antistatic - Custom Logo
Speed	Maximum opening speed up to 1,2 m/s			
	Closing speed 1,2 m/s			
Wind resistance	Up to Class 2 EN 12424			
Motor	Three-phase self-braking 230V or 400V			
Control panel	With push-button panel, mushroom head and current switch	Window	Standard: No section or up to 1 section	
Opening system	Standard: Button on the panel and one on the opposite side		Optional: over 1 section possibility of variation, sizes and formats depending on the door measurements	
	Optional: - Touchless button - Photocells - Radio Remote Control - Micro Switch - Magnetic Loop - Anemometer - Radar - Numeric keyboard - Traffic Light	Standard 1: Man in Attendance		
	Crankcase / Motor	Standard: Galvanized steel	Standard 2: Photocell and safety edge	
		Optional: - Galvanized steel powder coated - Stainless Steel 304/316	Standard 3: Light Curtain	
		Security System	Optional: - Safety edge - UPS - Acoustic Alarm - Counterweight	
			Operating temperature	From -25°C to + 70°C
		Life cycles	1.250.000	

RAL Standard for insulated Curtain

RAL Standard for Curtain

